

General

|                       |                             |
|-----------------------|-----------------------------|
| Productgroup          | PowerOne                    |
| Mounting type         | Massive Pressfit Techn      |
| Material              | Brass                       |
| Surface               | tin                         |
| Customs tariff number | 85369095                    |
| Country of origin     | Federal Republic of Germany |
| Weight per piecs ~    | 0.002600 kg                 |

Technical data

|                          |                     |
|--------------------------|---------------------|
| Terminal / Type          | blind hole / Metric |
| Thread/Diameter x Length | 3.000 mm x 3.50 mm  |
| Torque                   | 0.50 Nm             |

|                              |                    |
|------------------------------|--------------------|
| Socket length x Socket width | 7.000 mm x 7.00 mm |
| Socket height                | 6.00 mm            |
| Socket rounded               | yes                |
| Height total                 | 9.50 mm            |
| Height over pcb              | 6.00 mm            |
| No. of Pins                  | 9                  |
| Pin length                   | 3.50 mm            |
| Grid dimension X / Y         | 2.54 mm / 2.54 mm  |
| Pin alignment                | Full plain         |

Processing

|                 |                               |
|-----------------|-------------------------------|
| Press in force  | 360 N up to 2250 N            |
| Retention force | 60-80 % of press-in force     |
| Press-in speed  | 100 mm/min. up to 250 mm/min. |
| PCB thickness   | 1.60 mm up to 3.20 mm         |
| Notice          |                               |

Current carrying capacity

|                          |                     |
|--------------------------|---------------------|
| Part (20°C) ~ / (85°C) ~ | 90.000 A / 54.000 A |
|--------------------------|---------------------|

Usage and storage

|                    |                                                   |
|--------------------|---------------------------------------------------|
| Temperature        | -40°C up to +150°C                                |
| Storage            | dry environment protected from weather conditions |
| Storage conditions | at +5°C up to +40°C, 75% RH, non-condensing       |


Accessories

|               |  |
|---------------|--|
| Press in tool |  |
|---------------|--|

Co-applicable documents

|                         |                                 |
|-------------------------|---------------------------------|
| Powerelement Guidelines | Link to Powerelement Guidelines |
|-------------------------|---------------------------------|

Standard drill pattern








Drill hole specification for PCB

|         |  |                |                                                   |
|---------|--|----------------|---------------------------------------------------|
| Drill Ø |  | drill tool     | 1,60 mm                                           |
|         |  | drill hole     | 1,60 mm - 0,025 mm                                |
| Cu      |  | Cu – in Hole   | Average 30 µm – 60 µm<br>min. 25 µm, max. 80 µm * |
| End Ø   |  | HAL            | (1,450 mm +/- 0,05 mm)                            |
|         |  | chem. surfaces | (1,475 mm +/- 0,05 mm)                            |

Note: For Press-fit Technology drill diameter and copper thickness are fix. End Ø for reference only.

\* single measurement points in microsection

Dimensions



WÜRTH  
ELEKTRONIK  
MORE THAN  
YOU EXPECT

Würth Elektronik ICS GmbH & Co. KG  
Würthstraße1 74676 Niedernhall, Germany  
P +49 7940 9810-4444 powerelement@we-online.de  
www.powerelement.com

Observe protective note ISO 16016. Passing on or duplication without previous written agreement forbidden. Violations oblige to compensation. All rights reserved in the event of a patent or utility model protection. Subject to change without notice! Is NOT subject to change service!

Generaltolerances  
DIN ISO 2768-mH

Projection mode



|          |          |                 |
|----------|----------|-----------------|
| Revision | Date     | All measures in |
| D        | 13.06.25 | mm              |

Part no.

**K91093**

Description

**PowerOne Bush vertical blind hole**



REACH  
COMPLIANT



RoHS  
COMPLIANT