

General

Productgroup	PowerOne
Mounting type	THT
Material	Brass
Surface	tin
Customs tariff number	85369095
Country of origin	Federal Republic of Germany
Weight per pieces ~	0.030200 kg

Technical data

Terminal / Type	Bolt / Metric
Thread/Diameter x Length	6.000 mm x 10.00 mm
Torque	3.90 Nm

Socket length x Socket width	13.000 mm x 13.00 mm
Socket height	19.50 mm
Socket rounded	yes
Height total	33.00 mm
Height over pcb	29.50 mm
No. of Pins	25
Pin length	3.50 mm
Grid dimension X / Y	2.54 mm / 2.54 mm
Pin alignment	Full plain

Processing

Press in force	1000 N up to 6250 N
Retention force	60-80 % of press-in force
Press-in speed	100 mm/min. up to 250 mm/min.
PCB thickness	1.60 mm up to 3.20 mm
Notice	

Current carrying capacity

Part (20°C) ~ / (85°C) ~	250.000 A / 150.000 A
--------------------------	-----------------------

Usage and storage

Temperature	-40°C up to +150°C
Storage	dry environment protected from weather conditions
Storage conditions	at +5°C up to +40°C, 75% RH, non-condensing


Accessories

Press in tool

Co-applicable documents

Powerelement Guidelines	Link to Powerelement Guidelines
-------------------------	---------------------------------

Standard drill pattern






Drill hole specification for PCB

Cu		Cu – in Hole	Average min. 25 µm *
End Ø		HAL chem. surfaces	(1,800 mm +0,1 / -0,05 mm) (1,800 mm +0,1 / -0,05 mm)
Note:	For Press-fit Technology drill diameter and copper thickness are fix. End Ø for reference only.		

* single measurement points in microsection

Dimensions



**WÜRTH
ELEKTRONIK**
MORE THAN
YOU EXPECT

Würth Elektronik ICS GmbH & Co. KG
Würthstraße 1 74676 Niedernhall, Germany
P +49 7940 9810-4444 powerelement@we-online.de
www.powerelement.com

Observe protective note ISO 16016. Passing on or duplication without previous written agreement forbidden. Violations oblige to compensation. All rights reserved in the event of a patent or utility model protection. Subject to change without notice! Is NOT subject to change service!

General tolerances
DIN ISO 2768-mH

Projection mode



Revision	Date	All measures in
E	01.07.25	mm

Part no.

K93064

Description

PowerOne Bolt



REACH
COMPLIANT



RoHS
COMPLIANT