

General

Productgroup	PowerOne THT
Mounting type	THT
Material	Brass
Surface	tin-plated +
Customs tariff number	85369095
Country of origin	Federal Republic of Germany
Weight per pieces ~	0.003890 kg

Technical data

Terminal / Type	Bush through hole / Metric
Thread/Diameter x Length	5.000 mm x 7.00 mm
Torque	2.20 Nm

Socket length x Socket width	9.000 mm x 9.00 mm
Socket height	7.00 mm
Socket rounded	yes
Height total	11.00 mm
Height over pcb	7.50 mm
No. of Pins	4
Pin length	3.50 mm
Grid dimension X / Y	5.08 mm / 7.62 mm
Pin alignment	Full plann

Processing

Press in force	0 N up to 0 N
Retention force	
Press-in speed	0 mm/min. up to 0 mm/min.
PCB thickness	1.60 mm up to 3.20 mm
Notice	

Current carrying capacity

Part (20 °C) ~ / (85 °C) ~	64.000 A / 40.000 A
----------------------------	---------------------

Usage and storage

Temperature	-40 °C up to +150 °C
Storage	dry environment protected from weather conditions
Storage conditions	at +5 °C up to +40 °C, 75% RH, non-condensing


Accessories

Press in tool	
---------------	--

Co-applicable documents

Powerelement Guidelines	Link to Powerelement Guidelines
-------------------------	---------------------------------

Standard drill pattern






Drill hole specification for PCB




Cu		Cu – in Hole	Average min. 25 µm *
End Ø		HAL chem. surfaces	(1,800 mm +0,1 / -0,05 mm) (1,800 mm +0,1 / -0,05 mm)
Note:	For Press-fit Technology drill diameter and copper thickness are fix. End Ø for reference only.		

* single measurement points in microsection

Dimensions



A-A



**WÜRTH
ELEKTRONIK**
MORE THAN
YOU EXPECT

Würth Elektronik ICS GmbH & Co. KG
Würthstraße 1 74676 Niedernhall, Germany
P +49 7940 9810-4444 powerelement@we-online.de
www.powerelement.com

Observe protective note ISO 16016. Passing on or duplication without previous written agreement forbidden. Violations oblige to compensation. All rights reserved in the event of a patent or utility model protection. Subject to change without notice! Is NOT subject to change service!

General tolerances

DIN ISO 2768-mH

Projection mode



Revision

B

Date

23.06.25

All measures in

mm

Part no.

K96271

Description

PowerOne THT Bush vertical through hole



REACH
COMPLIANT



RoHS
COMPLIANT